

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Claims

In accordance with 37 CFR § 1.121, Applicants submit the following complete listing of all pending claims with markings for the currently amended claims.

Listing of the Claims:

1. (Currently Amended) A hazardous area warning system for warning personnel of an attendant hazard when they may enter into hazardous areas, said system comprising:

a receiver for receiving a directional signal indicating proximity of a hazard, and including circuitry that indicates a level of the received directional signal in a plurality of different directions;

means for determining based on the indicated levels of the received directional signal in the plurality of different directions whether a received signal indicates proximity to an attendant hazard;

and

means for transmitting in response to a determination that the received signal indicates proximity to an attendant hazard an indication signal indicating that ~~of whether~~ a person wearing said ~~directional receiving means~~ receiver is in a hazardous area.

2. (Original) A system as in claim 1, wherein said receiver comprises:

x-axis receiving means directed along a x-axis and receiving a signal from a hazard zone transmitter;

y-axis receiving means directed along a y-axis and receiving a signal from said hazardous zone transmitter;

z-axis receiving means directed along a z-axis and receiving a signal from said hazardous zone

transmitter, the x-, y-, and z-axes generally being mutually perpendicular to each other; and

means for combining received signals from said x-axis receiving means, said y-axis receiving means and z-axis receiving means.

3. (Original) A system as in claim 2, wherein each of said x-axis receiving means, said y-axis receiving means, and said z-axis receiving means comprises:

an antenna directed along a respective axis;

an amplifier receiving signal from said antenna;

a filter filtering an output from said amplifier; and

a detector detecting the output of said filter to determine whether a signal is present in said output.

4. (Original) A system as in claim 3, wherein said antenna is a ferrite rod wrapped in wire.

5. (Original) A system as in claim 3, wherein said determining means comprises a comparator, said comparator determining whether an output of said combining means indicates that said directional receiving means is closer than a first distance to said transmitter.

6. (Original) A system as in claim 5, wherein said comparator further determines whether said receiver is closer than a second distance to said transmitter.

7. (Original) A system as in claim 6, wherein said determining means further includes a caution output linked to a first output of a decoder, a danger output connected to a second output of said decoder and an encoder connected to said first output and said second output.

8. (Original) A system as in claim 7, wherein when said comparator determines said receiver is within said first distance, said comparator places an output signal on said caution output; and when said comparator determines said receiver is within said second distance, said comparator places an output signal on said danger output.

9. (Original) A system as in claim 8, wherein said encoder encodes any outputs placed on said caution output and said danger output.

10. (Original) A system as in claim 7, wherein said danger output comprises vibrating means for providing personnel with a tactile indication of danger.

11. (Original) A system as in claim 1, further comprising a data link receiver, said data link receiver comprising data receiver means receiving a signal from said transmitting means; decoder means decoding said received signal; driver means driving a plurality of outputs responsive to said decoder means; and indicator means indicating a safety state responsive to said driver means.

12. (Original) A system as in claim 11, wherein said indicator means includes a yellow light, a red light and a green light.

13. (Original) A system as in claim 12, wherein said yellow light, red light and green light are LEDs and, said indicator means further includes a green status link LED.

14. (Original) A system as in claim 13, further comprising means for disabling a system being monitored.

15. (Original) A system as in claim 13, further comprising a first data logger logging danger situation occurrences; and a second data logger logging caution condition occurrences.

16. (Original) A system as in claim 1, further comprising a warning transmitter, said warning transmitter including an antenna, said antenna being a ferrite rod wrapped in a loop of wire.

17. (Original) A system as in claim 16, wherein said warning transmitter further comprises an oscillator driving a resonant frequency; a buffer amplifier buffering said resonant frequency from said oscillator; and an antenna driver driving said resonant frequency onto said antenna.

18. (Currently Amended) A non-directional proximity receiver comprising:

a x-axis receiver having an antenna directed in a first direction;

a y-axis receiver having an antenna directed in a second direction, said second direction being perpendicular to said first direction;

a z-axis receiver having an antenna directed in a third direction, said third direction being perpendicular to the plane of said first direction and said second direction;

an adder combining signals from said x-axis receiver, said y-axis receiver and said z-axis receiver;

a comparator determining whether a received signal indicates an attendant hazard;

an encoder encoding said indication of an attendant hazard in response to a determination that the received signal indicates an attendant hazard; and

a transmitter transmitting said encoded indication.

19. (Original) A proximity receiver as in claim 18, wherein each of said x-axis receiver, said y-axis receiver and said z-axis receiver further comprises an amplifier receiving a signal from said antenna; a filter filtering output from said amplifier; and a detector detecting a signal in said filtered output, an output of said detector being an input to said adder.

20. (Original) A proximity receiver as in claim 19, wherein each of said x-axis antenna, said y-axis antenna and said z-axis antenna is a wire wrapped around a ferrite rod.

21. (Original) A proximity receiver as in claim 20, further comprising a caution

indicator connected to a first output of said comparator; and a danger indicator connected to a second output of said comparator.

22. (Original) A proximity receiver as in claim 21, wherein said danger indicator is a motor, vibrations from said motor providing an indication of danger.

23. (Previously Presented) A system as in claim 1 further comprising a data link receiver receiving the indication of whether a person wearing said directional receiving means is in a hazardous area as an encoded signal indicating a safety condition; a decoder decoding said received encoded signal; and a plurality of indicators indicating said safety condition.

24. (Original) A data link receiver as in claim 23, wherein said plurality of indicators include a danger zone indicator, a caution indicator and a normal indicator.

25. (Original) A data link receiver as in claim 23, wherein said plurality of indicators are a red light, yellow light and green light.

26. (Original) A data link receiver as in claim 25, wherein said red light, green light and yellow light are LEDs.